

## Modifications

### ANNEXES

#### 1. Annex 3.3.1.3 - Position of stations and service places on railway lines; main technical and operational characteristics

The following modifications were made:

Line number	It line number	Name of the service place	Statistical number of service place	Service place				Track												
				Staffless	Remote controlled	Signalling equipment	suitable for train crossing	Number/name	Function (passenger/ freight/ other)	Electrified (yes)	Length (m)	Through main line (yes)	Designated to go-round (yes)	length/width/height of platform (m)	Qualified as occupied by persons (yes)	Designated for storage	Preheating/precooling	Connection to electric power	Water supply	Connection to sewer
108/2	108	Kismacs-mh.																		
108/2	108	Látókép-mh.	14472	yes		none	no	1	passenger/ freight		200	yes		200/3,7/sk+15	yes	no				
108/2	108	Tófürdő-mh.	46425	yes		none	no	1	passenger/ freight		115	yes		115/2,3/sk+00	yes	no				
108/2	108	Gyóskérút-mh.	44024	yes		none	no	1	passenger/ freight		147	yes		147/2,5/sk+00	yes	no				
106/1	106	Szepes-mh.	14936	yes		none	no	1	passenger/ freight		145	yes		145/2,4/sk+00	yes	no				
106/1	106	Mikeperc-mh.	44016	yes		none	no	1	passenger/ freight		66	yes		66/4,8/sk+00	yes	no				

#### 2. Annex 3.8.2 - List of loading places on open access railway network - MÁV Zrt

The following modifications were made:

##### Budapest Regional Centre

Service place	Open access loading place registered by MÁV Zrt									Loading track next to loading places											Applicable speed (km/h)	Possibility of serving (S-straight, D-diverging position)	Restrictions
	Code of the service place	Position From section to section	Size Width (m) x length (m)	currently usable area (m2)	Paved yes / no	Material of pavement	Current technical condition	Lighting	Loading and other equipments	Name of the track	Usable length (m)	Loading length (m)	Branching-off turnout(s)		Availability of catenary		Derailer (pcs)	Scotch block (pcs)	Axle load (t)	Current technical state			
													Number	Switch operation mode	yes / no	Length (m)							
Székesfehérvár	03269		218x12	2616	yes	asphalt	good	lighted	none	Kertli-út-vg.	270	218	112	central	no	0	4	0	20		5	D	Can be served only from the end-point.
Székesfehérvár	03269		185x6	1110	yes	cobblestone	good	lighted	side-loading	XXVI-út-vg.	340	485	132+134+136	local	yes	340	0	0	20		10	D	

## Debrecen Regional Centre

Service place	Open access loading place registered by MÁV Zrt									Loading track next to loading places										Applicable speed (km/h)	Possibility of serving (S-straight, D-diverging position)	Restrictions	
	Code of the service place	Position	Size	Currently usable area (m <sup>2</sup> )	Paved	Material of pavement	Current technical state	Lighting	Loading and other equipments	Name of the track	Usable length (m)	Loading length (m)	Branching-off turnouts		Availability of catenary		Derailer (pcs)	Scotch block (pcs)	Axle load (t)				Current technical state
		From section to section	Width (m) - length (m)	yes - no	concrete-sealing	concrete-slab	side-loading	Number	Switch operation mode				yes - no	length (m)									
Csenger	15578	169-172	42 x 150	1800	yes	concrete-sealing	bad	lighted	none	I.-(A)-vágány	300	150	2	local	no	0	0	0	18,5	bad	5	D	"C"-group
Csenger	15578	169-172	10 x 12	120	yes	macadam	adequate	lighted	none	I.-(B)-vágány	300	12	2	local	no	0	0	0	18,5	bad	5	D	"C"-group
Csenger	15578	169-172	7 x 16	112	yes	concrete-slab	bad	lighted	side-loading	I.-(O)-vágány	300	16	2	local	no	0	0	0	18,5	bad	5	D	"C"-group
Debrecen	13912	2203-50-2206-50	10x300	3000	no	unpaved	adequate	unlighted	none	Répa-vágány	352	300	603	local	no	0	0	0	22,5	good	5	S	
Derecske	14051	64-35-65-00	21 x 65	1365	yes	concrete	adequate	lighted	none	I.-(A)-vágány	351,8	65	1-2	local	no	0	2	0	18,5	bad	10	D	"C"-group
Derecske	14051	66-10-67-35	11x95	1045	yes	asphalt	adequate	lighted	none	I.-(B)-vágány	351,8	95	1-2	local	no	0	2	0	18,5	bad	10	D	"C"-group
Fényeslitke	14134	496-00-498-90	8x290	2320	no	none	adequate	lighted	none	I. (A) vágány	780	290	13,16	Domino 55 electric central	yes	780	0	0	24,5	adequate	40	D	"C" group The loading place is prohibited to be used till 13 December 2014.
Görögzsállás	11494	337-50-338-50	8x80	640	no	none	adequate	lighted	none	I. (A) vágány	800	80	5,16	manual	yes	700	0	2	21	adequate	5	D	"C" group The loading place is prohibited to be used till 13 December 2014.
Görögzsállás	11494	342-50-344-00	5x250	1250	yes	ferroconcrete seating	adequate	lighted	none	I. (B) vágány	800	250	5,16	manual	yes	700	0	2	21	adequate	5	D	"C" group The loading place is prohibited to be used till 13 December 2014.
Görögzsállás	11494	342-50-344-00	5x25	125	yes	ferroconcrete seating	adequate	lighted	side loading	I. (O) vágány	800	25	5,16	manual	yes	700	0	2	21	adequate	5	D	"C" group The loading place is prohibited to be used till 13 December 2014.
Hajdúdorog	14696	369-02-369-72	13x70	910	yes	asphalt	adequate	lighted	none	I. (A) vágány	511	70	1, 2	local	no	0	0	2	21	adequate	40	D	"C" group The loading place is prohibited to be used till 13 December 2014.
Hajdúdorog	14696	370-39-370-69	13x30	390	yes	asphalt	adequate	lighted	none	I. (B) vágány	511	30	1, 2	local	no	0	0	2	21	adequate	40	D	"C" group The loading place is prohibited to be used till 13 December 2014.
Hajdúdorog	14696	371-01-371-37	13x36	468	yes	cobblestone	adequate	lighted	none	I. (C) vágány	511	36	1, 2	local	no	0	0	2	21	adequate	40	D	"C" group The loading place is prohibited to be used till 13 December 2014.
Hajdúsámson	15347	89-25-91-60	235 x 5	1175	yes	stone	adequate	lighted	none	III. vágány	332	235	2, 4, 1, 3	local/point wire	no	0	0	2	21	adequate	40	D	
Hajdúsámson	15347	91-60-92-10	50 x 10	500	yes	stone	adequate	lighted	side loading	III. (O) vágány	332	50	2, 4, 1, 3	local/point wire	no	0	0	2	21	adequate	40	D	
Hortobágy	14522	375-95-376-66	10x71	710	yes	concrete	good	lighted	none	IV.-vágány	196,05	71	2	local	no	0	0	0	21	good	5	S	"C"-group
Kisköre	12310	888-892	8x310	2480	yes	macadam	bad	lighted	none	V. vágány	312	310	8,7	manual	no	0	0	2	22,5	bad	5	D	The loading place is prohibited to be used till 13 December 2014.
Mándok	15875	783-791	10x25	250	yes	concrete	adequate	lighted	side-loading	I.-(O)-vágány	812	25	1-1	central-point-wire	no	0	0	0	21-1	average	10	D	"C"-group
Máriapócs	15146	290-00-291-00	10x70	700	yes	concrete	bad	lighted	none	I.-vágány	142	70	2-3	manual	no	0	1	0	18,5	bad	5	D	
Mezőpeterd	14431	1478 - 1481	9,1 x 360	3277	yes	asphalt	good	lighted	none	I. vágány	810	360	4, 1	central	no	0	0	0	21	adequate	20	D	Due to reconstruction, the loading place is not functioning as a public loading place till 13 December 2014.
Nagygyesed	15149	220-35-224-73	11 x 24	264	yes	stone-and-soil	adequate	lighted	side-loading	I.-(O)-vágány	524	24	2	manual	no	0	1	1	18,5	bad	5	D	"C"-group
Nagygyesed	15149	220-35-224-73	10 x 200	3600	yes-no	stone-and-soil	adequate	lighted	none	I.-vágány	524	400	2	manual	no	0	1	1	18,5	bad	5	D	"C"-group
Nagyhat	14408	142-50-142-70	12,5x20	250	yes	concrete	adequate	unlighted	none	I.-vágány	98,8	20	1-2	local	no	0	2	0	21	adequate	10	D	"C"-group
Nagyzeke	15784	316-60-318-70	8 x 10	80	yes	unpaved	adequate	unlighted	side-loading	I.-(O)-vágány	240	10	2	manual	no	0	0	2	18,5	average	5	D	"C"-group
Nagyzeke	15784	316-60-318-70	10x120	1200	yes	unpaved	adequate	unlighted	none	I.-vágány	240	120	2	manual	no	0	0	2	18,5	average	5	D	"C"-group
Nyírábrány	15180	291-30-294-00	8x270	2160	no	unpaved	adequate	unlighted	none	I.-a.-vágány	329	270	10-12	local	no	0	0	0	21	adequate	40	D	"C"-group
Nyírábrány	15180	292-75-299-00	15x28	420	yes	asphalt	adequate	lighted	none	I.-(A)-vágány	844	28	3	local	no	0	0	0	21	adequate	40	D	"C"-group
Nyírábrány	15180	292-75-299-00	8x18	144	yes	asphalt	adequate	lighted	side-loading	I.-(O)-vágány	844	18	3	local	no	0	0	0	21	adequate	40	D	"C"-group
Nyírábrány	15180	292-75-299-00	15x80	1200	yes	asphalt	adequate	lighted	none	I.-(B)-vágány	844	80	3	local	no	0	0	0	21	adequate	40	D	"C"-group

Tarcal	11460	115+00-116+00	4x100	400	yes	ferroconcrete-seating	adequate	lighted	side-loading	I.-vágány	300	400	10;25	central--	yes	300	0	2	21	adequate	5	D	Due-to-the-technical-state-of-the-switches-loading-track-is-out-of-traffic.
Tiszavasvári	14738	4+99-2+10	10x15	150	yes	concrete	bad	lighted	side-loading	AFOR-csonka	420	45	7	local	no	0	0	4	21	adequate	5	S	"K"-group
Tunyogmatolcs	15743	37+25--35+45	5 x 150	750	yes	asphalt	adequate	lighted	none	I.-vágány	489	450	2	manual	yes	0	0	2	18,5	average	5	D	"K"-group
Vámospercs	15164	204+05-505+05	10,2x40	408	yes	asphalt	adequate	lighted	side-loading	I.(O)vágány	470	40	3/A <sub>1</sub> -6	local	no	0	0	0	21	adequate	40	D	"K"-group
Vámospercs	15164	205+05-206+25	15x120	1800	yes	asphalt	adequate	lighted	none	I.-vágány	420	420	3/A <sub>1</sub> -6	local	no	0	0	0	21	adequate	40	D	"K"-group
Vásárosnamény	15933	533+70 - 535+10	25x150	3750	yes	asphalt	good	lighted	none	I.-vágány	650	150	2	central	no	0	0	0	22 t	bad	20	D	"K" group The loading place is prohibited to be used till 13 December 2014.
Vásárosnamény	15933	532+50 - 533+00	15x60	900	yes	concrete	good	lighted	side loading and end-loading	I.(O)vágány	650	60	2	central	no	0	0	0	22 t	bad	20	D	"K" group The loading place is prohibited to be used till 13 December 2014.
Vásárosnamény	15933	531+50 - 532+55	11x305	3355	yes	concrete	good	lighted	none	V.-vágány	751	305	2	central	no	0	0	0	22 t	bad	20	S	The loading place is prohibited to be used till 13 December 2014.
Vásárosnamény	15933	531+60 - 532+90	6 x 140	840	yes	cobblestone	good	lighted	end-loading	IX. vágány	148	140	16	central	no	0	0	0	22 t	good	20	S	The loading place is prohibited to be used till 13 December 2014.

## Szeged Regional Centre

Service place	Open access loading place registered by MÁV Zrt									Loading track next to loading places											Applicable speed (km/h)	Possibility of serving (S-straight, D-diverging position)	Restrictions
	Code of the service place	Position	Size	Currently usable area (m <sup>2</sup> )	Paved yes - no	Material of pavement	Current technical state	Lighting	Loading and other equipments	Name of the track	Usable length (m)	Loading length (m)	Branching-off turnouts		Availability of catenary		Derailer (pcs)	Scotch block (pcs)	Axle load (t)	Current technical state			
		From section to section	Width (m) - length (m)										Number	Switch operation mode	yes - no	length (m)							
Fülöpszállás	16238	776+50 - 777+00	20 x 50	1000	yes	stone	average	lighted		VI. (A)vágány	274	50	8	central	no	0	1	0	21	adequate	15	S	
Fülöpszállás	16238	777+50 - 779+00	20 x 150	3000	yes	concrete	average	lighted		VI. (B)vágány	274	150	8	central	no	0	1	0	21	adequate	15	S	
Fülöpszállás	16238	777+00 - 777+50	20 X 20	400	yes	concrete	average	lighted	livestock loading	VI. vágány	274	20	8	central	no	0	1	0	21	adequate	15	S	
Hódmezővásárhely	18572	1532—1539	16 x 242	3872	yes	stone	good	lighted		I.-(A)-vágány	250	242	4,9	local	no	0	0	0	21	good	40	D	
Hódmezővásárhely	18572	1532—1539	7,5 x 54	405	yes	stone	good	lighted		I.-(B)vágány	250	54	4,9	local	no	0	0	0	21	good	40	D	
Hódmezővásárhely	18572	1532—1539	7,5 x 54	405	yes	stone	good	lighted		X.-vágány	331	54	4,9	local	no	0	0	0	21	good	40	D	
Kardoskút	18358	513—514 513+38 - 513+73 513+73 - 514+38	29 x 50/35 29 x 65	325 1015 1885	yes	concrete asphalt stone	good average	lighted		I. vágány	324	50 35 65	5-6 6,5	local	no	0	0	2	17	bad good	5 40	D	
Kisszállás	16337	1446+55-1447+55	15 x 100	1500	no	soil	bad	lighted		VII.	110	100	14	local	no	0	0	0	21	good	15	S	
Kiskundorozsma	17194	5+00 - 6+10	5 x 110	550	no	soil	average	unlighted		Szállás II. vágány	200	110	I/2, II/1	local	no	0	0	1	21	good	10	D	
Kútvolgy	18580	1442—1444+20 1444+50 - 1444+10 1444+10 - 1443+30 1443+30 - 1442+00 1442+00 - 1442+00	8 x 270 7 x 40 7 x 80 4 x 70 4 x 60	2160 280 560 280 240	yes	concrete, asphalt concrete seating soil	good	unlighted		I. vágány	927	270 40 80 70 60	4+2 2,1	central	no	0	0	0	21	good	40	D	
Soltvadkert	14287	1100—1103	65 x 10	650	yes	asphalt	average	unlighted	side-loading	I.(O)-vágány	670	65	9	local	no	0	1	0	21	good	15	D	
Soltvadkert	14287	1103+06—1104+32	13 x 30	390	yes	stone	average	unlighted		I.-vágány	670	30	9	local	no	0	1	0	21	good	15	D	
Szeged—Rákus	18534	1779—1782	5 X 62	310	yes	stone	good	unlighted	side-loading	XVI.-(O2)Vágány	341	62	33;26	local	no	0	0	0	21	good	40	D	
Szeged—Rákus	18534	1779—1782	5 X 29	145	yes	stone	good	unlighted	side-loading	XVI.-(O1)Vágány	341	29	33;26	local	no	0	0	0	21	good	40	D	
Szeged—Rákus	18534	1779—1782	10 X 300	3000	yes	stone	good	unlighted		XVI.-Vágány	341	300	33;26	local	no	0	0	0	21	good	40	D	
Szeged—Rákus	18534	1779—1782	5 x 90	450	yes	stone	good	unlighted	side-loading	XVIII.-(O)Vágány	380	90	5;33	local	no	0	0	0	21	good	40	S	
Szeged—Rákus	18534	1779—1782	13 x 50	650	yes	stone	good	unlighted	end-loading	X.-(H)Vágány	65	50	33	local	no	0	0	0	21	good	40	S	

Téskömös	18324	616-617	10x40	400	yes	asphalt	bad	lighted	side-loading	I.-(O)vágány	330	40	2-3	local	no	0	0	2	17	bad	40	0	
----------	-------	---------	-------	-----	-----	---------	-----	---------	--------------	--------------	-----	----	-----	-------	----	---	---	---	----	-----	----	---	--

## Pécs Regional Centre

Service place	Open access loading place registered by MÁV Zrt									Loading track next to loading places												Restrictions	
	Code of the service place	Position	Size	Currently usable area (m <sup>2</sup> )	Paved	Material of pavement	Current technical state	Lighting	Loading and other equipments	Name of the track	Usable length (m)	Loading length (m)	Branching-off turnouts		Availability of catenary		Derailer (pcs)	Scotch block (pcs)	Axle load (t)	Current technical state	Applicable speed (km/h)		Possibility of serving (S-straight, diverging position)
		From section to section	Width (m) - length (m)		yes - no								Number	Switch operation mode	yes - no	length (m)							
Szántód-Köröshegy	03400	1272+00-1273+85	12,5 x 185	2 313	yes	macadam	good	lighted	no	I. (B)vágány	555	185	6, 7	central	yes	50+50	2	0	21	to be renewed	10	D	It is prohibited to be used till 31 May 2015.
Szántód-Köröshegy	03400	1275+03-1276+13	16 x 110	1 760	yes	macadam	good	lighted	no	I. (A) vágány	555	110	6, 7	central	yes	50+50	2	0	21	to be renewed	10	D	It is prohibited to be used till 31 May 2015.

## 3. Annex 3.8.4 - Refuelling facilities

The following modifications were made:

Regional Storage Centre, Site of Supply	Code of the service place	Sale of Diesel oil	Service time
Hatvan	11025	yes	Mon-Fri: <del>10:00-11:00</del> - 01:00 Sat-Sun: 13:00-01:00
Kiskunhalas	16311	yes	Mon-Fri: <del>04:00-12:00</del> 03:00-15:00
Komárom	01222	yes	Mon-Fri: <del>07:00-20:00</del> 11:00-24:00 Sat-Sun: <del>12:00-20:00</del> 16:00-24:00
Szentes	18184	yes	Mon-Sun: <del>06:00-00:30</del> 01:30

