

### Conditions for forwarding of loading units of combined traffic

Unified marking and coding of railway lines concerned in forwarding of loading units of combined transportation - large size containers, semi trailers and swap bodies (hereafter KV) - as well as conditions of forwarding are defined by UIC Leaflet 596-6, Loading Rules, Volume 2, point 9, and special agreements concluded with railway companies. Considering the above mentioned, loading units of combined traffic specified above may only be accepted (taken over) for transportation and may be forwarded on the network of MÁV Zrt under conditions as follows:

a) **Large size containers:** Containers with width and height dimensions of 8' x 8' (2438x2438 mm), 8' x 8'6" (2438x2591 mm) and 8' x 8'6 1/2" (2438x2603 mm) may be forwarded as normal consignments.

In accordance with Loading Rules, Volume 2, Point 9, Table 1 (hereafter Table 1) swap bodies for the railway network operated by MÁV Zrt, based on data of code tables, may be transported as normal consignments.

b) **High-cube containers** with width and height dimensions of 8' x 9'6" (2438x2896 mm) shall be taken into account with C 45 code number.

c) Should the container not comply with specification laid down in table 1, it can be transported as an out-of-gauge consignment with special acceptance (take-over) permit, or as a consignment of type 11 in compliance with a special international agreement by taking point 'f' into consideration.

For forwarding of an exceptional consignment an Rk permit must be issued.

d) **Semi-trailers:** Width of semi-trailers, marked with UIC code number and satisfying provisions of UIC Leaflets, equals to that of swap bodies.

Height of semi-trailers are marked on the UIC code table with a letter "P" and a two-digit number for semi trailers of a width of 2550 mm and with a three-digit number for semi trailers of a width of 2600 mm.

Semi trailers may be forwarded on the network of MÁV Zrt as a normal consignment if code number on the UIC code table is not higher than the relevant code number of Table 1.

Semi-trailers may be transported as an out-of-gauge consignment type 11 if the code number is higher than the relevant code number in Table 1, but not higher than P 80 or P 410 by taking into consideration point f). Also the correction value written on the vehicle must be taken into consideration.

e) **Swap bodies:** The letter "C" and a two-digit number on the UIC code table show swap bodies up to the width of 2550, and a three-digit number shows swap bodies of a width of 2600 mm.

Swap bodies may be forwarded on the network of MÁV Zrt as a normal consignment if the code number on the UIC code table is not higher than the relevant code number of Table 1. Swap bodies may be transported as an out-of-gauge consignment type 11 if the code number is higher than the relevant code number in Table, but code number is at least P 80 or P 410 by taking into consideration point f). Also the correction value written on the vehicle must be taken into consideration.

#### f) Transportation of out-of-gauge KV loading units

1. Loading units of combined traffic under points c), d), e) may be forwarded as a consignment of type 11 in accordance with the route defined in the delivered timetable with the exception of stations and line sections as follows:

- Budapest-Déli pu. – Kelenföld,
- Hidas-Bonyhád – Bátaszék,
- Pilisvörösvár – Piliscsaba,
- Szarvaskő – Bélapátfalva – Királd,
- Veszprémvarsány – Zirc,
- Kisköre – Abádszalók,
- Abaújszántó mrh. – Hidasnémeti,
- Szokolya – Diósjenő –Drégelypalánk.

2. This regulation applies to forwarding of transport units of combined traffic. MÁV Rk-20/ completed with the very last two digits of the actual year (e.g. 20/14, 20/15) shall be introduced on the consignment note and on the label “U”.

3. Out-of -gauge KV loading units without UIC code table and those that cannot meet conditions mentioned here, can be accepted (taken over) and forwarded only as exceptional consignment, or on the basis of special agreement and special permit.

Loading rules - Volume 2, Point 9 Table 1													
UTI (in general without exceeding loading gauge) may be forwarded as normal consignment on MÁV lines, if													
code number of swap bodies/containers/rolling container bodies on UIC code-plates, or rating code or type number of high size containers are not higher than the code number, type number given by the Table depending on wagons													
		2-axle wagons		Bogie wagons								Railway vehicle with wagon-type mark	
		K...	L...s	R...s				S...s					
		maximum axle distance		maximum distance between bogie pins bb								 	
		8 m	9 m	9 m	14,86 m				11,30 m	15,80 m			
		maximum distance from the outermost axle outwards (na)											
		2,25 m	2 m	2 m	2 m	2 m	2 m	2 m	2 m	2 m	2 m	2 m	
		maximum height of loading surface											
		1250 mm	1180 mm	1260 mm	1180 mm	1240 mm	1260 mm	1300 mm	1180 mm	1180 mm	1240 mm		
		loading inaccuracy											
		± 20 mm	± 10 mm	± 10 mm				± 10 mm					
UIC-code no	rail way	with guide stick	with fastening equipment	with lateral guide or with fastening equipment				with fastening equipment					
55	MAV <sup>6)</sup>	C 21 / C 340	C32 / C351	C 24 / C 343	C 19 / C 338	C 13 / C 332	C 11 / C 330	C 07 / C...	C 28 / C 347	C 18 / C 337	C 12 / C 331	C 21 / C 340	B 21 / B 340

4. <sup>6)</sup> except BUDAPEST-DÉLI PU