

ANNEXES

1. Annex 3.8.2 - List of loading places on open access railway network - MÁV Zrt

The following modifications were made:

Budapest Regional Centre

Service place	Open access loading place registered by MÁV Zrt									Loading track next to loading places										Applicable speed (km/h)	Possibility of serving (S-straight, D-diverging position)	Restrictions	
	Code of the service palce	Position	Size	currently usable area (m2)	Paved	Material of pavement	Current technical condition	Lighting	Loading and other equipments	Name of the track	Usable length (m)	Loading length (m)	Branching-off turnout(s)		Availability of catenary		Derailer (pcs)	Scotch block (pcs)	Axle load (t)				Current technical state
		From section to section	Width (m) x length (m)		yes / no								Number	Switch operation mode	yes / no	Length (m)							
Kispest	+10419-10199	82+07-83+27	5 x 4	20	yes	concrete	average	unlighted	end loading	IV. vágány	86	86	13	local	no	0	0	0	21	poor	10	D	
Kispest	+10419-10199	82+07-83+27	5 x4	20	yes	concrete	average	unlighted	end loading	V. vágány	86	86	15	local	no	0	0	0	21	poor	10	D	
Kispest	+10419-10199	82+07-83+27	5 x4	20	yes	concrete	average	unlighted	end loading	VI.vágány	177	177	21	local	no	0	0	0	21	poor	10	D	
Kispest	+10419-10199	81+00-82+00	120x5	600	no	none	average	unlighted	none	VII. vágány	160	120	19	local	no	0	0	0	21	poor	10	D	
Kispest	+10419-10199	1242+65-1243+60	60 x 2	120	yes	concrete	average	unlighted	side loading	I.vágány	672	60	11	local	no	0	0	0	21	poor	10	D	
Rákospalota Újpest	+11440-10140	42/43	30,8 x 80	2464	yes	stone	average	lighted	nincsenek	31. csónkavágány	300	80	31	manual	no	0	0	0	20	adequate	5	S	
Soroksár	+10332-10322		43x24	1032	no	-	average	unlighted	side loading	I. (A)vágány	766	43	20, 9	central	no	0	1	0	20	poor	10	D	
Soroksár	+10332-10322		10x10	100	no	-	average	unlighted	side loading	I. (O)vágány	766	10	20, 9	central	no	0	1	0	20	poor	10	D	
Soroksár	+10332-10322		75x10	750	no	-	average	unlighted	side loading	I.(B) vágány	766	75	20, 9	central	no	0	1	0	20	poor	10	D	
Tápiószecső	+1684-11627	588+42-595+92	4,5 x 140	630	yes	concrete+soil	bad	lighted	none	I.vágány	393	140	11	electric	no	0	1	1	21	poor	5	S	

Miskolc Regional Centre

Service place	Open access loading place registered by MÁV Zrt									Loading track next to loading places													Restrictions
	Code of the service place	Position	Size	Currently usable area (m ²)	Paved	Material of pavement	Current technical state	Lighting	Loading and other equipments	Name of the track	Usable length (m)	Loading length (m)	Branching-off turnouts		Availability of catenary		Derailer (pcs)	Scotch block (pcs)	Axle load (t)	Current technical state	Applicable speed (km/h)	Possibility of serving (S-straight, D-diverging position)	
		From section to section	Width (m) - length (m)		yes - no								Number	Switch operation mode	yes - no	length (m)							
Bánréve	11849-12849	452+00 - 453+40	20 × 140	2800	no	-	average	unlighted	scales	XV. csónka vágány	300	140	32	local	no	-	0	0	21	adequate	10km/h	D	
Bánréve	11849-12849	453+80 - 454+10	13 × 24	312	yes	broken stone	average	lighted	side loading	XV. csónka (O)vágány	300	24	32	local	no	-	0	0	21	adequate	10km/h	D	

Szeged Regional Centre

Service place	Open access loading place registered by MÁV Zrt									Loading track next to loading places										Applicable speed (km/h)	Possibility of serving (S-straight, D-diverging position)	Restrictions	
	Code of the service place	Position	Size	Currently usable area (m ²)	Paved	Material of pavement	Current technical state	Lighting	Loading and other equipments	Name of the track	Usable length (m)	Loading length (m)	Branching-off turnouts		Availability of catenary		Derailer (pcs)	Scotch block (pcs)	Axle load (t)				Current technical state
		From section to section	Width (m) - length (m)		yes - no								Number	Switch operation mode	yes - no	length (m)							
Orosháza	18614	1242+87 - 1243+70	12 x 73	876	yes	concrete	bad	lighted	side-and-end- loading side loading	I. (OH-O1) vágány	860	73	22, 23	local	no	0	0	0	21	bad	40	S	
Orosháza	18614	1242+87 - 1243+71	9 x 29	261	yes	concrete	bad	lighted	side loading	I. (O2) vágány	860	29	22, 23	local	no	0	0	0	21	bad	40	S	
Orosháza	18614	1242+87 - 1243+70 1236 - 1244	8,9 X 83 14 x 170	-739- 3119	yes	concrete asphalt	bad	lighted	side-and end loading	XVI. (OH) (H) vágány	104	-104- 83	22	local	no	0	0	0	21	bad	-40- 5	S	
Orosháza	18614	1236 - 1244	14 x 170	2380	yes	asphalt	bad	lighted		XVI. vágány	104	83	22	local	no	0	4	2	24	average	5	S	

2. Annex 3.8.4 - Refuelling facilities

The following modification was made:

Regional Storage Centre, Site of Supply	Code of the service place	Service time
Hatvan	11025 11205	Mon-Fri: 11:00-01:00 Sat-Sun: 13:00-01:00