



Coordinates of clearance basic data

GA loading gauge			GB loading gauge			MÁV loading gauge		International loading gauge		GC profile	
140	-750	-1500	-750	140	-1500	0	130	1450	430	-750	140
130	-750	-1500	-750	130	-1500	678,5	130	1575	430	-750	130
130	-1010	-2020	-1010	130	-2020	678,5	0	1575	3175	-1010	130
230	-1180	-2360	-1180	230	-2360	678,5	-10	1530	3300	-1180	230
230	-1225	-2450	-1225	230	-2450	700	-10	1486	3400	-1225	230
400	-1410	-2820	-1410	400	-2820	700	0	1434	3500	-1410	400
400	-1490	-2980	-1490	400	-2980	831,5	0	1372	3600	-1490	400
430	-1490	-2980	-1490	430	-2980	831,5	130	1301	3700	-1490	430
430	-1575	-3150	-1575	430	-3150	1220	130	1217	3800	-1575	430
3220	-1575	-3150	-1575	3220	-3150	1520	430	1118	3900	-1575	3500
3850	-1280	-2560	-1280	4080	-2560	1575	430	1000	4000	-1455	4650
4050	-1010	-2020	-460	4320	-920	1575	3500	400	4280	1455	4650
4320	-460	-920	460	4320	920	1395	3805	-400	4280	1575	3500
4320	460	920	1280	4080	2560	690	4650	-1000	4000	1575	430
4050	1010	2020	1575	3220	3150	-690	4650	-1118	3900	1490	430
3850	1280	2560	1575	430	3150	-1395	3805	-1217	3800	1490	400
3220	1575	3150	1490	430	2980	-1575	3500	-1301	3700	1410	400
430	1575	3150	1490	400	2980	-1575	430	-1372	3600	1225	230
430	1490	2980	1410	400	2820	-1520	430	-1434	3500	1180	230
400	1490	2980	1225	230	2450	-1220	130	-1486	3400	1010	130
400	1410	2820	1180	230	2360	-831,5	130	-1530	3300	750	130
230	1225	2450	1010	130	2020	-831,5	0	-1575	3175	750	140
230	1180	2360	750	130	1500	-700	0	-1575	430	-750	140
130	1010	2020	750	140	1500	-700	-10	-1450	430		
130	750	1500	-750	140	-1500	-678,5	-10				
140	750	1500	0	55		-678,5	0				
140	-750	-1500				-678,5	130				
						0	130				

130	-1575	-1575	55
4320	1575	1575	4320