

Modification**ANNEXES****1. Annex 3.8.2 - List of loading places on open access railway network - MÁV Zrt**

The following modifications were made:

Budapest Regional Directorate

Service place	Open access loading place registered by MÁV Zrt										Loading track next to loading places										Applicable speed (km/h)	Possibility of serving (S-straight, D-diverging position)	Restrictions
	Code of the service place	Position	Size	currently usable area (m2)	Paved	Material of pavement	Current technical conditon	Lighting	Loading and other equipments	Name of the track	Usable length (m)	Loading length (m)	Branching-off turnout(s)		Avallability of catenary		Derailer (pcs)	Scotch block (pcs)	Axle load (t)	Current technical state			
		From section to section	Width (m) x length (m)		yes / no								Number	Switch operation mode	yes / no	Length (m)							
Győr - Rendező	01289 01271	1403+16-1404+16	150x9,20x7,5	1500	yes	cobblestone	good	unlighted	none	Temető II. vágány	191	150	456	manual	no	0	0	0	21	adequate	5	S	
Győr - Rendező	01289 01271	1403+72-1405+40	19x94	1786	yes	cobblestone	adequate	lighted	end loading	Csárda csonka	60	19	424	manual	no	0	0	0	21	adequate	5	S	
Győr - Rendező	01289 01271	1404+00-1405+63	75x19, 70x6,5, 70x6	2300	yes	cobblestone	adequate	lighted	none	Csárda III	64	64	428	manual	no	0	0	0	21	adequate	5	S	
Győr - Rendező	01289 01271	1404+16-1406+03	132x6	792	yes	cobblestone	adequate	lighted	none	Csárda IV	156	132	428	manual	no	0	0	0	21	adequate	5	S	
Győr - Rendező	01289 01271	37+50-37+71	62x13, 70x6,5	1261	yes	cobblestone	adequate	lighted	none	Csárda V	167	132	427	manual	no	0	0	0	21	adequate	5	S	

Szeged Regional Directorate

Service place	Open access loading place registered by MÁV Zrt									Loading track next to loading places											Applicable speed (km/h)	Possibility of serving (S-straight, D-diverging position)	Restrictions
	Code of the service place	Position	Size	Currently usable area (m ²)	Paved	Material of pavement	Current technical state	Lighting	Loading and other equipments	Name of the track	Usable length (m)	Loading length (m)	Branching-off turnouts		Availability of catenary		Derailer (pcs)	Scotch block (pcs)	Axle load (t)	Current technical state			
		From section to section	Width (m) - length (m)		yes - no								Number	Switch operation mode	yes - no	length (m)							
Hódmezővásárhely	18572	1537+74 - 1538+14	15 x 40	600	yes	stone	good	lighted		I.b vágány	736	40	4,9	local	no	0	0	0	21	bad	10	D	Loading restriction between 20.06.2016 00:00 - 04.07.2016 00:00
Hódmezővásárhely	18572	1538+75 - 1539+55	16 X 80	1600	yes	stone	good	lighted	side loading	I./b (O)vágány	736	80	4,9	local	no	0	0	0	21	bad	10	D	
Hódmezővásárhely	18572	1538+55 - 1538+20	15 x 35	525	yes	stone	good	lighted	end loading	XII. (H)vágány	30	30	30	local	no	0	0	0	21	bad	5	S	
Hódmezővásárhely	18572	1534+30	400	5200	yes	stone	good	lighted		XI. vágány	571	400	3	local	no	0	0	0	21	bad	5	S	Loading restriction between 20.06.2016 00:00 - 04.07.2016 00:00
Kútvolgy	18580	1444+50 - 1444+10	7 x 40	280	yes	concrete asphalt concrete seating soil	good	unlighted		I. (A)vágány	927	40 80 70 60	2,1	central	no	0	0	0	21	good	40	D	
		1444+10 - 1443+30	7 x 80	560																			
		1443+30 - 1442+60	4 x 70	280																			
		1442+60 - 1442+00	4 x 60	240																			
Kútvolgy	18580	1443 - 1445	14,6 x 90,7	1321	yes	asphalt	good	unlighted		I. (B)vágány	927	90,7	1,2	central	no	0	0	0	21	good	40	D	Loading restriction between 13.04.2016 08:00 - 04.07.2016 00:00
Székkutas	18598	1353+71 - 1348+81	6,5 x 490	3185	yes	stone	good	unlighted	side loading	I. vágány	798	490	3,4	local	no	0	0	2	21	bad	5	D	